

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier**

- Trade name: **COLOR SOLUTIONS BASECOAT EXCLUSIVES SKYLINE GREY STAGE 2**
- Article number: 113177
- UFI: C4S2-W0JK-4000-9T7D

1.2 Relevant identified uses of the substance or mixture and uses advised against

- Sector of Use
 - SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
 - SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- Product category PC9a Coatings and paints, thinners, paint removers
- Process category PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities
- Environmental release category ERC2 Formulation into mixture
- Article category AC1 Vehicles
- Application of the substance / the mixture
 - Coating compound/ Surface coating/ paint
 - Surface protection

1.3 Details of the supplier of the safety data sheet

- Manufacturer/Supplier:
 - HB BODY S.A.
 - B' ENTRANCE BLOCK 50 DA9 & MB6 Str
 - THESSALONIKI INDUSTRIAL AREA
 - 57.022, SINDOS
 - THESSALONIKI,GREECE
 - Ph: +30 2310 790 000
 - Fax: +30 2310 790 033
 - www.hbbody.com
 - email: hbbody@hbbody.com

- Further information obtainable from:
 - HB BODY S.A.
 - B' ENTRANCE BLOCK 50 DA9 & MB6 Str
 - THESSALONIKI INDUSTRIAL AREA
 - 57.022, SINDOS
 - THESSALONIKI,GREECE
 - Ph: +30 2310 790 000
 - Fax: +30 2310 790 033
 - www.hbbody.com
 - email: hbbody@hbbody.com

1.4 Emergency telephone number:

- Regional Medicines and Poisons Information Centre NI
- Pharmacy Department, Royal Hospital Suite
- Grosvenor Road Belfast
- Telephone: +44 28 90 63 2032
- Fax: +44 28 90 24 80 30
- Emergency telephone: 844 892 0111
- E-mail address: nirdic.nirdic@belfasttrust.hscni.net
- Members of the public seeking specific information on poisons should contact:
 - In England and Wales: NHS 111 - dial 111
 - In Scotland: NHS 24 - dial 111

Trade name: COLOR SOLUTIONS BASECOAT EXCLUSIVES SKYLINE GREY STAGE 2**SECTION 2: Hazards identification****2.1 Classification of the substance or mixture**

Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS02 GHS07

Signal word Warning

Hazard-determining components of labelling:

n-butyl ester

1-methoxy-2-propanol

Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

Results of PBT and vPvB assessment

This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT). This mixture contains no substance that is considered to be very persistent or very bioaccumulating (vPvB).

PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients**3.2 Chemical characterisation: Mixtures**

Description: Mixture of hazardous substances listed below with nonhazardous additions.

Continue on page 3
GB

Trade name: COLOR SOLUTIONS BASECOAT EXCLUSIVES SKYLINE GREY STAGE 2**Dangerous components:**

CAS: 123-86-4	n-butyl ester	45-<50%
EINECS: 204-658-1	Flam. Liq. 3, H226	
Index number: 607-025-00-1	STOT SE 3, H336	
RTECS: AF 7350000		
Reg.nr.: 01-2119485493-29-007		
01-2119485493-29-004		
01-2119485493-29-003		
01-2119485493-29-005		
01-2119485493-29		
CAS: 13463-67-7	titanium dioxide	15-<20%
EINECS: 236-675-5	Carc. 2, H351	
Index number: 022-006-00-2	Note: V, W, 10	
CAS: 1330-20-7	xylene	1-<5%
EINECS: 215-535-7	Flam. Liq. 3, H226	
Index number: 601-022-00-9	Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	
RTECS: ZE 2100000	Note: C	
Reg.nr.: 01-2119488216-32-001		
01-2119488216-32-002		
01-2119488216-32-003		
CAS: 107-98-2	1-methoxy-2-propanol	1-<5%
EINECS: 203-539-1	Flam. Liq. 3, H226	
Index number: 603-064-00-3	Acute Tox. 3, H331	
RTECS: UB 7700000	STOT SE 3, H336	
CAS: 100-41-4	ethylbenzene	1-<5%
EINECS: 202-849-4	Flam. Liq. 2, H225	
Index number: 601-023-00-4	STOT RE 2, H373; Asp. Tox. 1, H304	
RTECS: DA 0700000	Acute Tox. 4, H332	
CAS: 872-50-4	1-methyl-2-pyrrolidone	≥0-<0.3%
EINECS: 212-828-1	Repr. 1B, H360D	
Index number: 606-021-00-7	Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	
RTECS: UY 5790000	Specific concentration limit: STOT SE 3; H335: C ≥ 10 %	

SVHC

872-50-4 1-methyl-2-pyrrolidone

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures**4.1 Description of first aid measures**

General information: Immediately remove any clothing soiled by the product.

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Immediately rinse with water.

After eye contact: Rinse opened eye for several minutes under running water.

After swallowing: If symptoms persist consult doctor.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

Trade name: COLOR SOLUTIONS BASECOAT EXCLUSIVES SKYLINE GREY STAGE 2**SECTION 5: Firefighting measures****5.1 Extinguishing media**

- Suitable extinguishing agents:
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet

· **5.2 Special hazards arising from the substance or mixture** No further relevant information available.

5.3 Advice for firefighters

Firefighters should always protective equipment and breathing apparatus when handling fire coming from these products

5.6 Fire and explosion Hazards**Speial protective equipment and fire fighting procedures:**

Firefighters should wear full protective flameproof clothing and self contained breathing apparatus for the firefighter if necessary. In the event of any fire try cool down the tanks with water spray. If possible do not allow the water used by firefighters to enter the drains or come in any contact with the water supply lines for the public. Always seek as appropriate.

- Additional information Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities**Storage:**

- Requirements to be met by storerooms and receptacles: Store outdoors.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.

· **7.3 Specific end use(s)** No further relevant information available.

Trade name: COLOR SOLUTIONS BASECOAT EXCLUSIVES SKYLINE GREY STAGE 2**SECTION 8: Exposure controls/personal protection****8.1 Control parameters**

- Ingredients with limit values that require monitoring at the workplace:

123-86-4 n-butyl esterWEL Short-term value: 966 mg/m³, 200 ppmLong-term value: 724 mg/m³, 150 ppm**1330-20-7 xylene**WEL Short-term value: 441 mg/m³, 100 ppmLong-term value: 220 mg/m³, 50 ppm

Sk; BMGV

107-98-2 1-methoxy-2-propanolWEL Short-term value: 560 mg/m³, 150 ppmLong-term value: 375 mg/m³, 100 ppm

Sk

100-41-4 ethylbenzeneWEL Short-term value: 552 mg/m³, 125 ppmLong-term value: 441 mg/m³, 100 ppm

Sk

872-50-4 1-methyl-2-pyrrolidoneWEL Short-term value: 80 mg/m³, 20 ppmLong-term value: 40 mg/m³, 10 ppm

Sk

- Regulatory information WEL: EH40/2020

- Ingredients with biological limit values:

1330-20-7 xylene

BMGV 650 mmol/mol creatinine

Medium: urine

Sampling time: post shift

Parameter: methyl hippuric acid

- Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

- Personal protective equipment:

- General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

- Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Continue on page 6

GB

Trade name: COLOR SOLUTIONS BASECOAT EXCLUSIVES SKYLINE GREY STAGE 2

- Penetration time of glove material
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:
The breakthrough time of gloves is unknown for this product itself. The glove material that can be used is recommended on the basis of the different substances in the preparation.
- For the permanent contact gloves made of the following materials are suitable: Fluorocarbon rubber (Viton)
- For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:
Rubber gloves
- Eye protection:



Tightly sealed goggles

- Body protection: Protective work clothing

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

· General Information

· Appearance:

Form: Fluid
Colour: Different according to colouring

- Odour: Characteristic
- Odour threshold: Not determined.
- pH-value: Mixture is non-soluble (in water).

· Change in condition

Melting point/freezing point: Undetermined.
Initial boiling point and boiling range: 124-128 °C (123-86-4 n-butyl ester)

- Flash point: 23 - 60 °C
- Flammability: Flammable.
- Autoignition temperature: 370 °C
- Decomposition temperature: Not determined.
- Ignition temperature: Product is not selfigniting.
- Explosive properties: Risk of explosion by shock, friction, fire or other sources of ignition.
- Explosion limits:
 - Lower: 1.1 Vol %
 - Upper: 7.5 Vol %
- Vapour pressure at 20 °C: 10.7 hPa
- Density at 20 °C: 0.988 g/cm³
- Relative density: Not determined.
- Vapour density: Not determined.
- Evaporation rate: Not determined.
- Solubility in / Miscibility with water: Not miscible or difficult to mix.
- Partition coefficient: n-octanol/water: Not determined.

Continue on page 7
GB

Trade name: COLOR SOLUTIONS BASECOAT EXCLUSIVES SKYLINE GREY STAGE 2

- Viscosity:
 - Dynamic: Not determined.
 - Kinematic at 20 °C: 0 mm²/s
- Solvent content:
 - Organic solvents: 57.7 %
 - VOC (EC) 570.3 g/l
 - Solids content (volume): 19.0 %
- **9.2 Other information** No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
 - Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
 - Acute toxicity Based on available data, the classification criteria are not met.
 - LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Dermal LD50 42,265 mg/kg (rabbit)
Inhalative LC50/4 h 122 mg/l

123-86-4 n-butyl ester

Oral LD50 13,100 mg/kg (rat)
Dermal LD50 >5,000 mg/kg (rabbit)
Inhalative LC50/4 h >21 mg/l (rat)

13463-67-7 titanium dioxide

Oral LD50 >20,000 mg/kg (rat)
Dermal LD50 >10,000 mg/kg (rabbit)
Inhalative LC50/4 h >6.82 mg/l (rat)

1330-20-7 xylene

Oral LD50 4,300 mg/kg (rat)
Dermal LD50 2,000 mg/kg (rabbit)
Inhalative LC50/4 h 11 mg/l (ATE)

107-98-2 1-methoxy-2-propanol

Oral LD50 5,660 mg/kg (rat)
Dermal LD50 13,000 mg/kg (rabbit)
Inhalative LC50/4 h 6 mg/l (rat)

100-41-4 ethylbenzene

Oral LD50 3,500 mg/kg (rat)
Dermal LD50 17,800 mg/kg (rabbit)

Trade name: COLOR SOLUTIONS BASECOAT EXCLUSIVES SKYLINE GREY STAGE 2

Inhalative LC50/4 h 11 mg/l (ATE)

872-50-4 1-methyl-2-pyrrolidone

Oral LD50 3,914 mg/kg (rat)

Dermal LD50 8,000 mg/kg (rabbit)

- Primary irritant effect:
- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Additional toxicological information:
- CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure
May cause drowsiness or dizziness.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information**12.1 Toxicity**

- Aquatic toxicity:

This product is not toxic for the aquatic life. Nevertheless do not dispose the product or any cleaning solvents used along with this product into the sea

- **12.2 Persistence and degradability**

This product contains polyesteric molecules and organic solvents and is not known to be bioaccumulative. It can be considered as biodegradable in small quantities. In case of disposal, it should be treated as a hazardous material and should be disposed accordingly. Do not just throw it away

- **12.3 Bioaccumulative potential** No further relevant information available.

- **12.4 Mobility in soil** No further relevant information available.

- Additional ecological information:

- General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- **12.5 Results of PBT and vPvB assessment**

- PBT: This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT).

- vPvB: This mixture contains no substance that is considered to be very persistent or very bioaccumulating (vPvB).

- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**

- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- European waste catalogue

HP3 Flammable

HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

HP7 Carcinogenic

Continue on page 9

GB

Trade name: COLOR SOLUTIONS BASECOAT EXCLUSIVES SKYLINE GREY STAGE 2

- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information**14.1 UN-Number**

- ADR, IMDG, IATA UN1263

14.2 UN proper shipping name

- ADR UN1263 PAINT
- IMDG, IATA PAINT

14.3 Transport hazard class(es)

- ADR



- Class 3 (F1) Flammable liquids.
- Label 3
- IMDG, IATA



- Class 3 Flammable liquids.
- Label 3

14.4 Packing group

- ADR, IMDG, IATA III

14.5 Environmental hazards:

- Marine pollutant: No

14.6 Special precautions for user

- Warning: Flammable liquids.
- Hazard identification number (Kemler code): 30
- EMS Number: F-E,S-E
- Stowage Category A

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

- Transport/Additional information: Not applicable.

- ADR

- Limited quantities (LQ) 5L
- Excepted quantities (EQ) Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml

- Transport category 3
- Tunnel restriction code D/E

- IMDG
- Limited quantities (LQ) 5L

Trade name: COLOR SOLUTIONS BASECOAT EXCLUSIVES SKYLINE GREY STAGE 2

- Excepted quantities (EQ) Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml
- UN "Model Regulation": UN 1263 PAINT, 3, III

SECTION 15: Regulatory information

•3Y

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- None of the ingredients is listed.
- Poisons Act
- Regulated explosives precursors
7664-38-2 phosphoric acid: 30%
- Regulated poisons
None of the ingredients is listed.
- Reportable explosives precursors
None of the ingredients is listed.
- Reportable poisons
None of the ingredients is listed.
- Labelling according to Regulation (EC) No 1272/2008
The product is classified and labelled according to the GB CLP regulation.
- Hazard pictograms



GHS02 GHS07

-
- Signal word Warning
- Hazard-determining components of labelling:
n-butyl ester
1-methoxy-2-propanol
- Hazard statements
H226 Flammable liquid and vapour.
H336 May cause drowsiness or dizziness.
- Precautionary statements
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P241 Use explosion-proof [electrical/ventilating/lighting] equipment.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 71, 72

Trade name: COLOR SOLUTIONS BASECOAT EXCLUSIVES SKYLINE GREY STAGE 2

- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II
None of the ingredients is listed.
- REGULATION (EU) 2019/1148
- Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))
None of the ingredients is listed.
- Annex II - REPORTABLE EXPLOSIVES PRECURSORS
None of the ingredients is listed.
- Regulation (EC) No 273/2004 on drug precursors
None of the ingredients is listed.
- Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors
None of the ingredients is listed.
- National regulations:
- Other regulations, limitations and prohibitive regulations
- Substances of very high concern (SVHC) according to UK REACH
872-50-4 1-methyl-2-pyrrolidone
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has been carried out.

SECTION 16: Other information

This information is based on our current knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H331 Toxic if inhaled.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer.
H360D May damage the unborn child.
H373 May cause damage to organs through prolonged or repeated exposure.
- Classification according to Regulation (EC) No 1272/2008
Flammable liquids
Bridging principles
Specific target organ toxicity (single exposure) The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.
- Department issuing SDS: Department of Quality Control
- Contact:
HB BODY S.A
Ms Olympia Stamkou
Ph: +30 2310 790 032
fax: +30 2310 790 033
email: stamkou@hbbody.com

Continue on page 12

GB

Trade name: COLOR SOLUTIONS BASECOAT EXCLUSIVES SKYLINE GREY STAGE 2

· * Data compared to the previous version altered.

GB
Continue on page 13

Trade name: COLOR SOLUTIONS BASECOAT EXCLUSIVES SKYLINE GREY STAGE 2**Annex: Exposure scenario****Short title of the exposure scenario****Sector of Use**

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category PC9a Coatings and paints, thinners, paint removers**Process category PROC8a** Transfer of substance or mixture (charging and discharging) at non-dedicated facilities**Article category AC1** Vehicles**Environmental release category ERC2** Formulation into mixture**Description of the activities / processes covered in the Exposure Scenario**

See section 1 of the annex to the Safety Data Sheet.

Conditions of use According to directions for use.**Duration and frequency** Frequency of use:**Physical parameters**

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

Physical state Fluid**Concentration of the substance in the mixture** The substance is main component.**Used amount per time or activity** Smaller than 100 g per application.**Other operational conditions****Other operational conditions affecting environmental exposure** Use only on hard ground.**Other operational conditions affecting worker exposure**

Avoid contact with the skin.

Do not breathe gas/vapour/aerosol.

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

Avoid contact with eyes.

Other operational conditions affecting consumer exposure No special measures required.**Other operational conditions affecting consumer exposure during the use of the product** Not applicable.**Risk management measures****Worker protection****Organisational protective measures**

Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

Technical protective measures

Use product only in enclosed systems.

Ensure that suitable extractors are available on processing machines

Provide explosion-proof electrical equipment.

Personal protective measures

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Pregnant women should strictly avoid inhalation or skin contact.

Avoid contact with the eyes.

Tightly sealed goggles

Continue on page 14

GB

Trade name: COLOR SOLUTIONS BASECOAT EXCLUSIVES SKYLINE GREY STAGE 2

- **Measures for consumer protection**
 - Ensure adequate labelling.
 - Observe consumer information and advice on safe use.
- **Environmental protection measures**
- **Water**
 - Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.
 - Do not allow to reach sewage system.
- **Soil**
 - Prevent contamination of soil.
 - The product is only processed over the concrete collecting basin.
- **Disposal measures** Ensure that waste is collected and contained.
- **Disposal procedures**
 - Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Waste type** Partially emptied and uncleaned packaging
- **Exposure estimation**
- **Consumer**
 - This product is to be used by professional technicians only.
 - Not relevant for this Exposure Scenario.
- **Guidance for downstream users**
 - Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.